



SUPREME COMFORT PAD

Stall Measurements:

1. Each stall is measured center post to center post
2. When pads are made for tie stall barns, production will take into account extra width on the frame for triple bend legs and post frames.
 - a. If there is a barn post, the comfort pad will be made wider on that side to compensate any cutting that is needed.
3. Free Stall barns are also measured center to center. There are very few posts involved with a free stall barn. Pads are made to be brisket board compatible.
4. Pads can extend to the edge of the gutter, or to the edge of the grates in a flush system free stall barn or tie stall barn.
5. Best slant on concrete for self-cleaning is 2 to 3 inches from head to tail.

Installation:

1. Pads are slid into place. Only two anchors are required to hold the pad secure. Using a drill and a hammer jack to fasten the anchors into the concrete.
 - a. The anchors are 3" long and made of stainless steel.
2. Circle blades can be used to cut a hole for the posts or for the triple bend legs.
3. Pads should not be installed butted tightly against each other. There should be a ½" gap to allow mats to expand in the summer.
4. If there is an open space between the installed pads, the farmer may wish to use strips of rubber mats, or pieces of treated wood to fill in the spaces. It is good to fill these spaces so a cow will not get their hoof caught and break a leg.

Bedding:

1. A small amount of bedding is fine. Sand may cause an abrasive type situation.

Warranty:

1. Pad has a 5 year limited warranty on them.
2. When an order is shipped, an original copy of the warranty will go to the end-user and to the dealer. Humane also keeps a copy of the warranty on file for future reference.
3. Any pad installed by the end-user and the mat has been cut so the foam is exposed makes the warranty null and void.

Important Note:

The use of udder or bag balm should not be used in contact with our mats as it is hard to remove and will cause the mats to swell. **Any** product that contains animal, mineral, or vegetable oil in it will have the same result. We recommend the following: for cleaning and disinfecting, use *alcohols, teat dips, or 1% or less solutions of soap, detergent, or bleach*. For softeners and lubricants, use *glycerin, glycols, or silicone & castor oils*. A good one to use is a solution of **2 parts Witch Hazel** and **1 part Glycerin**. This is a mild astringent, anti-irritant, antiseptic that moisturizes.